

Shell Tellus C22 PDF

Introduction to Shell Tellus C22: The Premium Hydraulic Oil Solution

shell tellus c22 is a leading hydraulic oil formulation designed to meet the demanding needs of modern industrial machinery. As industries evolve, the importance of reliable, high-performance lubricants becomes paramount to ensure equipment longevity, efficiency, and safety. Shell Tellus C22 stands out as a top-tier hydraulic oil that combines advanced additive technology with high-quality base oils, providing optimal performance across a variety of applications. Whether in manufacturing plants, construction equipment, or mobile machinery, Shell Tellus C22 offers a comprehensive solution to enhance operational productivity and reduce maintenance costs.

In this comprehensive guide, we will delve into the key features, benefits, applications, and technical specifications of Shell Tellus C22, helping you make an informed decision for your hydraulic system needs.

Understanding Hydraulic Oils and Their Importance

What Are Hydraulic Oils?

Hydraulic oils are specialized lubricants used in hydraulic systems to transfer power efficiently, lubricate moving parts, and prevent corrosion and wear. They are vital in ensuring the smooth operation of machinery such as excavators, presses, injection molding machines, and other industrial equipment.

Why Quality Matters in Hydraulic Oils

Using high-quality hydraulic oils like Shell Tellus C22 ensures:

- Reduced equipment wear and tear
- Improved system efficiency
- Lower maintenance costs
- Enhanced safety and reliability
- Extended machinery lifespan

Choosing the right hydraulic oil is crucial to prevent issues such as foaming, oxidation, and deposit formation, which can impair system performance.

Features and Benefits of Shell Tellus C22

Key Features

- High-Performance Additive Technology: Shell Tellus C22 contains advanced additives that provide excellent wear protection and oxidation stability.
- Premium Base Oils: Made from carefully selected base oils to ensure low volatility and high thermal stability.
- Anti-Wear and Anti-Corrosion Properties: Protects hydraulic components from premature wear and corrosion.
- Excellent Demulsibility: Ensures rapid separation of water from the oil, reducing the risk of emulsions.
- Good Compatibility: Compatible with many sealing materials and other lubricants, minimizing system contamination.

Major Benefits

- Enhanced Equipment Durability: Provides robust protection for hydraulic components, extending service intervals.
- Superior Hydraulic Performance: Maintains optimal viscosity for efficient power transfer.
- Reduced Operating Costs: Less downtime and lower maintenance expenses due to improved reliability.
- Environmental Compatibility: Meets industry standards for environmental safety and sustainability.
- Versatility: Suitable for a wide range of hydraulic systems operating under various temperature and load conditions.

Technical Specifications of Shell Tellus C22

Parameter	Specification
---	---
Viscosity Grade	ISO 32 and ISO 46 (depending on application)
Viscosity Index	Typically above 100
Flash Point	Generally above 200°C

| Pour Point | Typically below -15°C |

| Oxidation Stability | Excellent, ensuring long oil life |

| Anti-Wear Performance | Meets or exceeds industry standards such as DIN 51524 Part 2 |

| Compatibility | Compatible with most sealing materials and other hydraulic oils |

Note: Always refer to the product datasheet for detailed specifications tailored to your specific application.

Applications of Shell Tellus C22

Shell Tellus C22 is designed to deliver optimal performance in various industrial and mobile hydraulic systems. Its versatility makes it suitable for:

Industrial Hydraulic Systems

- Manufacturing machinery
- Injection molding equipment
- Presses and stamping machines
- Machine tools

Mobile Hydraulic Equipment

- Construction machinery (excavators, loaders)
- Agricultural machinery
- Material handling equipment
- Mining equipment

Specialized Uses

- Hydraulic systems requiring long oil life
- Equipment operating under high load and temperature conditions
- Systems demanding high wear protection

Why Choose Shell Tellus C22 Over Other Hydraulic Oils?

Superior Performance and Reliability

Shell Tellus C22 is formulated with proprietary additives that outperform many conventional hydraulic oils, ensuring your equipment runs smoothly and efficiently.

Proven Track Record

With decades of experience in lubricant formulation, Shell offers products backed by extensive research, testing, and real-world performance data.

Environmental and Safety Standards

Shell is committed to sustainability, and Tellus C22 complies with industry standards for environmental safety, making it a responsible choice for modern facilities.

Cost-Effectiveness

The durability and efficiency benefits of Shell Tellus C22 translate into reduced maintenance costs and minimized downtime, providing excellent value over the product's lifespan.

How to Properly Use and Maintain Shell Tellus C22

Application Guidelines

- Ensure the hydraulic system is clean before filling.
- Use the recommended viscosity grade (ISO 32 or ISO 46) based on your equipment specifications.
- Follow the manufacturer's instructions for oil change intervals.
- Regularly monitor oil condition and viscosity to detect early signs of contamination or degradation.

Storage Recommendations

- Store in a clean, dry, and cool environment.
- Keep containers tightly sealed when not in use.
- Avoid exposure to direct sunlight and extreme temperatures to preserve oil quality.

Environmental and Safety Considerations

Shell Tellus C22 is formulated to meet stringent safety and environmental standards. Proper handling and disposal are essential to minimize environmental impact. Always follow local regulations and best practices for lubricant disposal.

Conclusion: Making the Most of Shell Tellus C22

Choosing the right hydraulic oil is vital for maintaining the efficiency, safety, and longevity of your machinery. Shell Tellus C22 stands out as an industry-leading solution, offering exceptional performance, reliability, and value. Its advanced formulation ensures optimal protection against wear, oxidation, and corrosion, making it suitable for a wide range of industrial and mobile hydraulic applications.

Investing in Shell Tellus C22 can lead to significant operational benefits, including extended equipment life, reduced downtime, and lower maintenance costs. For businesses seeking a dependable, high-quality hydraulic oil, Shell Tellus C22 is an excellent choice that aligns with industry standards and environmental considerations.

Where to Purchase Shell Tellus C22

Shell products are widely available through authorized distributors, industrial supply stores, and online platforms. When purchasing Shell Tellus C22, ensure you buy from reputable sources to guarantee product authenticity and quality.

Final Thoughts

In summary, Shell Tellus C22 is a premium hydraulic oil designed to meet the rigorous demands of modern machinery. Its blend of high-quality base oils and advanced additives provides unparalleled protection and performance, making it a smart investment for any industrial operation aiming for efficiency and durability.

For more information or to request a quote, contact your local Shell representative or visit the official Shell website. Proper selection and maintenance of hydraulic oils like Shell Tellus C22 will ensure your equipment operates smoothly, safely, and efficiently for years to come.

Shell Tellus C22: An In-Depth Review of a Premier Hydraulic Oil Solution

In the realm of industrial machinery and hydraulic systems, the choice of lubricants plays a pivotal role in ensuring operational efficiency, longevity, and safety. Among the myriad options available, Shell Tellus C22 stands out as a premium hydraulic oil designed to meet the demanding needs of modern machinery. This comprehensive review delves into the composition, features, applications, and performance characteristics of Shell Tellus C22, offering industry professionals and enthusiasts

a detailed understanding of this product.

Understanding Shell Tellus C22

What is Shell Tellus C22?

Shell Tellus C22 is a high-performance, anti-wear hydraulic oil formulated to deliver exceptional lubrication, oxidation stability, and wear protection. It belongs to Shell's renowned Tellus series, which is widely recognized across industries for reliable hydraulic system performance. C22 indicates its viscosity grade, aligning with ISO 32 or ISO 46 standards, depending on regional classifications, making it suitable for a broad spectrum of hydraulic applications.

Key Attributes and Specifications

- Viscosity Grade: ISO VG 32/46, adaptable for various machinery requirements.
- Base Oil Composition: Mineral oil-based, with carefully selected additives.
- Additive Technology: Incorporates anti-wear agents, rust and oxidation inhibitors, and rust inhibitors.
- Performance Standards: Meets or exceeds industry standards such as DIN 51524 Part 2, ISO 11158, and API GL-1.

Composition and Technology

Base Oil Characteristics

Shell Tellus C22 utilizes high-quality mineral oils that provide excellent lubricating properties. These base oils are refined to remove impurities, ensuring consistent viscosity and thermal stability. The mineral oil base offers reliable performance across a range of operational temperatures, though it is primarily designed for moderate to heavy-duty applications.

Advanced Additive Package

The additive technology embedded within Shell Tellus C22 enhances its performance attributes:

- Anti-wear agents: Protect moving parts from premature wear, extending equipment lifespan.
- Oxidation inhibitors: Prevent oil degradation during prolonged operation, reducing sludge and deposit formation.
- Rust and corrosion inhibitors: Safeguard hydraulic components against moisture-induced corrosion.

- Demulsifiers: Facilitate efficient separation of water from oil, minimizing contamination risks.

This combination results in a lubricant that maintains its protective qualities under demanding operational conditions.

Performance Features and Benefits

Enhanced Wear Protection

One of Shell Tellus C22's primary advantages is its ability to form a durable lubricating film on metal surfaces, minimizing metal-to-metal contact. This reduces component wear, especially in high-load systems, and ensures machinery operates smoothly over extended periods.

Oxidation and Thermal Stability

The oil's resistance to oxidation minimizes the formation of sludge, varnish, and acid buildup. Its thermal stability allows it to withstand high operating temperatures without significant breakdown, maintaining viscosity and lubrication efficacy.

Corrosion Resistance and Water Separation

The rust and corrosion inhibitors protect hydraulic components from moisture-induced deterioration. Additionally, efficient demulsification properties facilitate water separation, reducing the risk of hydraulic system failure due to water contamination.

Energy Efficiency and Cost Savings

By reducing wear and maintaining optimal viscosity, Shell Tellus C22 can contribute to lower energy consumption, reducing operational costs over time. Its long service life also diminishes maintenance frequency and expenses.

Applications and Compatibility

Industrial Hydraulic Systems

Shell Tellus C22 is suitable for a wide range of industrial machinery, including:

- Plastic moulding machines
- Construction equipment
- Manufacturing presses

- Material handling systems

Its versatility makes it a preferred choice across sectors like manufacturing, mining, and transportation.

Compatibility with Equipment

This hydraulic oil is compatible with most hydraulic system materials, including seals, hoses, and pumps. However, it is crucial to consult equipment manufacturer guidelines to ensure compatibility, especially with systems that have specific lubricant requirements.

Operational Conditions

While Shell Tellus C22 performs reliably under typical conditions, it is especially advantageous in:

- Moderate to high-temperature environments
- Systems requiring anti-wear protection
- Applications with frequent water exposure

Comparison with Other Hydraulic Oils

Versus Mineral Oils

Compared to standard mineral oils, Shell Tellus C22 offers superior additive technology, resulting in better wear protection, oxidation stability, and water separation. Its formulation extends oil change intervals and reduces maintenance.

Versus Synthetic Alternatives

Synthetic hydraulic oils generally provide better performance in extreme temperatures and longer service life. However, Shell Tellus C22 strikes a balance between cost and performance, making it an economical choice for many applications without compromising essential protective features.

Market Positioning

Shell Tellus C22 is positioned as a premium mineral hydraulic oil, suitable for applications where reliability and protection are paramount but where synthetic oils may not be economically justified.

Operational and Maintenance Considerations

Oil Change Intervals

The oil's stability allows for extended drain intervals, typically ranging from 1,000 to 2,000 hours of operation, depending on system conditions and load.

Monitoring and Testing

Regular analysis of oil condition—checking parameters such as viscosity, particle contamination, and water content—helps optimize maintenance schedules and prevent system failures.

Storage and Handling

Proper storage in sealed containers away from contaminants ensures the oil maintains its quality. Handling precautions include avoiding exposure to moisture and extreme temperatures.

Sustainability and Environmental Impact

Environmental Considerations

Shell Tellus C22, like other mineral oils, poses environmental risks if spilled or improperly disposed of. However, Shell emphasizes responsible handling, and the product's formulation aims to minimize environmental impact during its lifecycle.

Recycling and Disposal

Disposal of used oil must adhere to local regulations. Recycling options are available, and Shell provides guidance to ensure environmentally responsible practices.

Conclusion: Is Shell Tellus C22 the Right Choice?

Shell Tellus C22 embodies a blend of technological innovation, reliable performance, and cost-effectiveness, making it a compelling option for a wide range of hydraulic systems. Its advanced additive package ensures superior wear protection, oxidation resistance, and water separation, which are crucial for maintaining machinery efficiency and longevity.

For industries seeking a high-quality hydraulic oil that balances performance with economic considerations, Shell Tellus C22 offers a dependable solution. Its compatibility with various equipment and operational environments further enhances its appeal.

Ultimately, selecting the right hydraulic oil depends on specific system requirements and operational conditions. However, Shell Tellus C22's proven track record and comprehensive performance

features position it as a top contender in the field of industrial lubricants.

Disclaimer: Always consult manufacturer specifications and technical datasheets before selecting or replacing hydraulic oils to ensure compatibility and optimal performance.

Question What are the key features of the Shell Tellus C22 hydraulic oil? Shell Tellus C22 is a high-performance hydraulic oil designed to provide excellent lubrication, corrosion protection, and oxidation stability, suitable for a wide range of industrial hydraulic systems. **Is Shell Tellus C22 compatible with other hydraulic oils?** Shell Tellus C22 is formulated to meet specific specifications and can generally be used in systems requiring ISO 32 hydraulic oils. However, it's recommended to consult equipment manufacturer guidelines before mixing with other oils. **What applications are best suited for Shell Tellus C22?** Shell Tellus C22 is ideal for industrial hydraulic systems, including manufacturing machinery, mobile equipment, and other applications where high performance and protection are required. **How does Shell Tellus C22 contribute to equipment longevity?** By providing excellent anti-wear properties, oxidation stability, and corrosion protection, Shell Tellus C22 helps extend the lifespan of hydraulic components and reduces maintenance costs. **What are the storage recommendations for Shell Tellus C22?** Store Shell Tellus C22 in a cool, dry, and well-ventilated area, away from direct sunlight and incompatible materials. Ensure containers are tightly sealed to prevent contamination. **Where can I purchase Shell Tellus C22 hydraulic oil?** Shell Tellus C22 can be purchased through authorized Shell distributors, industrial supply stores, or directly from Shell's official channels. **It's recommended to buy from reputable sources to ensure product authenticity.**

Related keywords: shell tellus c22, engine oil, motor oil, synthetic oil, vehicle lubrication, automotive oil, engine maintenance, car oil specifications, motor oil brands, engine performance

Shell Tellus 33 Specs

shell tellus 33 specs

The Shell Tellus 33 is a high-quality hydraulic oil renowned for its reliable performance, advanced formulation, and suitability for a wide range of industrial applications. As part of Shell's extensive range of lubricants, the Tellus 33 is specifically engineered to meet the demanding needs of hydraulic systems, ensuring smooth operation, protection against wear, and efficient energy transfer. Understanding the specifications of Shell Tellus 33 is essential for engineers, maintenance professionals, and equipment operators seeking optimal performance and longevity of their machinery. This in-depth article explores the detailed specifications of Shell Tellus 33, including its technical properties, performance standards, applications, and benefits.

Overview of Shell Tellus 33

Shell Tellus 33 is a mineral-based hydraulic oil formulated with advanced additives to deliver excellent lubrication, oxidation stability, and corrosion protection. It is designed to operate efficiently across a broad temperature range and under varying load conditions, making it a versatile choice for hydraulic systems in construction, manufacturing, and mobile equipment.

Technical Specifications of Shell Tellus 33

Understanding the technical specifications of Shell Tellus 33 provides insight into its performance capabilities and compatibility with different machinery.

Physical and Chemical Properties

The key physical and chemical properties of Shell Tellus 33 include:

- **Viscosity at 40°C:** Approximately 33 cSt (centistokes)
- **Viscosity at 100°C:** Around 6.0 cSt
- **Density at 15°C:** About 0.88 g/cm³
- **Flash Point (COC):** Typically over 200°C, ensuring safety during handling and storage
- **Pour Point:** Usually around -21°C, indicating good low-temperature performance
- **Fire Point:** Exceeds 220°C

Performance Standards and Approvals

Shell Tellus 33 meets or exceeds several international standards and specifications, ensuring its suitability for various applications:

- **ISO 11158:** Type HM (Hydraulic Mineral Oil)
- **DIN 51524 Part 2:** HVLP (High Viscosity, Low Pour Point)
- **Denison HF-0 / HF-2 / HF-4:** Approved, indicating compatibility with Denison hydraulic systems
- **ISO 6743-4:** Hydraulic fluids, HM category
- **API Service Classification:** Suitable for industrial hydraulic systems requiring a high-performance mineral oil

Viscosity and Temperature Range

The viscosity of Shell Tellus 33 is a critical factor influencing its performance and application scope.

Viscosity Grades and Selection

Shell Tellus 33, as indicated by its name, has a viscosity of approximately 33 cSt at 40°C, making it suitable for systems requiring medium viscosity oils. The viscosity index (VI) of the product indicates its stability across temperature variations, with typical values around 95-100, which helps maintain consistent film thickness in the hydraulic system.

Operational Temperature Range

The oil's pour point of -21°C and high flash point over 200°C allow it to operate efficiently in cold climates and high-temperature environments. It maintains good flow characteristics at low temperatures and provides sufficient thermal stability at elevated temperatures, ensuring reliable system performance.

Performance Characteristics of Shell Tellus 33

The effectiveness of Shell Tellus 33 is derived from its advanced formulation and additive package, which provide numerous performance advantages.

Oxidation Stability

The oil resists oxidation and sludge formation, extending the service life of hydraulic systems and reducing maintenance costs. Its high oxidation stability minimizes deposit formation, which can impair system efficiency.

Wear Protection

Additives in Shell Tellus 33 form protective films on moving parts, reducing metal-to-metal contact and wear. This enhances component lifespan and reduces downtime.

Corrosion and Rust Inhibition

The product contains corrosion inhibitors that protect hydraulic system components from rust and corrosion, especially in humid or contaminated environments.

Foam Control and Air Release

Shell Tellus 33 exhibits excellent foam control properties and air release characteristics, vital for maintaining hydraulic efficiency and preventing cavitation.

Applications of Shell Tellus 33

Shell Tellus 33 is suitable for a broad array of hydraulic systems, owing to its balanced viscosity and performance traits.

Industrial Machinery

- Manufacturing presses
- Conveyor systems
- Machine tools

Mobile Equipment

- Construction machinery
- Agricultural equipment
- Material handling vehicles

Marine and Offshore

- Hydraulic systems in ships
- Offshore platform machinery

Specialized Systems

- Hydraulic presses
- Lift systems
- Excavators

Benefits of Using Shell Tellus 33

Choosing Shell Tellus 33 offers several advantages that contribute to the efficiency and longevity of hydraulic systems.

- **Extended Oil Life:** High oxidation stability reduces oil degradation over time.
- **Enhanced Equipment Protection:** Superior wear and corrosion resistance safeguard system components.
- **Consistent Performance:** Stable viscosity across temperature ranges ensures reliable operation.

- **Energy Efficiency:** Reduced internal friction leads to lower energy consumption.
- **Environmental Safety:** Meets safety standards with high flash point and low volatility.

Compatibility and Maintenance Considerations

Proper compatibility and maintenance are vital for maximizing the benefits of Shell Tellus 33.

System Compatibility

- Compatible with most hydraulic system materials, including seals, hoses, and metals.
- Recommended for use in systems requiring ISO 11158 HM type oils.

Oil Change and Monitoring

- Follow manufacturer guidelines for oil change intervals.
- Regularly monitor viscosity, contamination, and additives to ensure optimal performance.
- Use filters designed for hydraulic oils to remove debris and water contamination.

Conclusion

Shell Tellus 33 is a high-performance hydraulic oil that combines robust technical specifications with proven performance standards. Its viscosity profile, oxidation stability, wear protection, and compatibility make it an ideal choice for diverse industrial and mobile applications. By understanding the detailed specifications of Shell Tellus 33, users can ensure their hydraulic systems operate efficiently, reliably, and with extended service life. Whether in manufacturing plants, construction sites, or marine environments, Shell Tellus 33 offers the performance and protection necessary to meet demanding operational requirements.

Shell Tellus 33 Specs: An In-Depth Review of Its Performance and Applications

When it comes to hydraulic fluids, selecting the right lubricant is crucial for ensuring optimal performance, equipment longevity, and safety. Among the myriad options available, Shell Tellus 33 stands out as a premium hydraulic oil trusted by industries worldwide. This comprehensive review dives deep into the specifications, properties, applications, and benefits of Shell Tellus 33, providing an extensive understanding for engineers, maintenance teams, and procurement professionals.

Introduction to Shell Tellus 33

Shell Tellus 33 is a high-quality, anti-wear hydraulic oil formulated to meet the demanding needs of

modern hydraulic systems. It is designed to deliver excellent lubrication, oxidation stability, and cleanliness, thereby extending equipment life and reducing downtime.

Key Highlights:

- Developed by Shell, a leading global lubricant manufacturer.
- Suitable for a broad range of hydraulic applications.
- Meets or exceeds industry standards such as ISO 32 and DIN 51524 Part 2.

Physical and Chemical Properties of Shell Tellus 33

Understanding the physical and chemical attributes of Shell Tellus 33 provides insight into its performance capabilities.

Viscosity

- Kinematic Viscosity at 40°C: Approximately 33 mm²/s (centistokes).
- Viscosity Grade: ISO 32 (indicating its viscosity class).
- Viscosity Index (VI): Typically around 100, reflecting good viscosity stability across temperature variations.

This viscosity level allows the oil to provide effective lubrication while ensuring system responsiveness, especially suitable for moderate to high-pressure hydraulic systems.

Density and Specific Gravity

- Density at 15°C: ~0.88 g/cm³.
- Specific Gravity: About 0.88, aiding in predicting flow and lubrication characteristics.

Flash Point and Fire Resistance

- Flash Point: Typically above 200°C (392°F), indicating good thermal stability and safety during operation.
- Fire Resistance: Meets industry safety standards, suitable for environments with stringent fire safety requirements.

Oxidation and Thermal Stability

- Designed to resist oxidation, thereby minimizing sludge and deposit formation.
- Maintains stability under high temperature operation, ensuring consistent performance over extended periods.

Demulsibility and Water Separation

- Exhibits excellent water separation properties, vital for hydraulic systems prone to moisture exposure.
- Quick separation of water from oil reduces corrosion risks and hydraulic system contamination.

Anti-wear and Additive Content

- Contains anti-wear additives to protect system components under boundary lubrication conditions.
- Incorporates rust and oxidation inhibitors for enhanced equipment protection.

Industry Standards and Approvals

Shell Tellus 33 conforms to several international standards, confirming its quality and compatibility:

- ISO 11158: Hydraulic fluid classification ISO 32.
- DIN 51524 Part 2: Lubricant for hydraulic systems.
- AGMA 9005-E02: Suitable for industrial gear oils.
- ASTM D6158: Performance in hydraulic applications.
- Compatibility: Compatible with various pump materials, seals, and hoses.

Applications of Shell Tellus 33

Given its versatile properties, Shell Tellus 33 is suited for a wide array of hydraulic systems across multiple industries.

Industrial Hydraulic Systems

- Manufacturing equipment
- Machine tools
- Steel mills
- Construction machinery

Agricultural Machinery

- Tractors and harvesters
- Hydraulic lifts and loaders

Mobile Equipment

- Excavators
- Cranes
- Material handling equipment

Marine and Offshore

- Hydraulic controls on ships
- Offshore drilling platforms

Steel and Mining Industries

- Hydraulic presses
- Conveyors
- Crushers

Performance Benefits of Shell Tellus 33

Choosing Shell Tellus 33 offers numerous advantages that contribute to efficient and reliable hydraulic system operation.

Enhanced Equipment Longevity

- The anti-wear additives prevent metal-to-metal contact.
- Oxidation stability reduces deposit formation, protecting pumps and valves.

Operational Efficiency

- Stable viscosity across temperature ranges ensures consistent hydraulic response.

- Good demulsibility minimizes water contamination, reducing corrosion and wear.

Cost-Effectiveness

- Longer oil drain intervals due to oxidation stability.
- Reduced maintenance costs and downtime.

Environmental and Safety Compliance

- Meets safety standards with high flash points.
- Formulated with environmentally considerate additives.

Usage Guidelines and Maintenance

Proper handling and maintenance optimize the performance of Shell Tellus 33.

Storage Recommendations:

- Store in clean, dry, and covered containers.
- Protect from extreme temperatures and contamination.

Application Tips:

- Use compatible filters and seals to prevent contamination.
- Follow recommended oil change intervals as per equipment manufacturer guidelines.

Monitoring and Testing:

- Regularly check viscosity, water content, and cleanliness.
- Conduct oil analysis to track additive depletion and contamination levels.

Comparison with Other Hydraulic Oils

While Shell Tellus 33 is highly regarded, understanding how it stacks against competitors is valuable.

| Aspect | Shell Tellus 33 | Competitor A | Competitor B |

|-----|-----|-----|-----|

| Viscosity Grade | ISO 32 | ISO 32 | ISO 32 |

| Oxidation Stability | Excellent | Good | Fair |

| Water Separation | Fast | Moderate | Slow |

| Additive Package | Advanced anti-wear | Basic | Moderate |

| Compatibility | Broad (seals, materials) | Limited | Moderate |

This comparison highlights Shell Tellus 33’s superior oxidation stability and water separation, making it a preferred choice in demanding applications.

Environmental and Regulatory Considerations

Shell is committed to sustainability and environmental responsibility. Shell Tellus 33 complies with:

- VOC Regulations: Low volatility to reduce emissions.
- REACH Compliance: Meets European chemical safety standards.
- Disposal Guidelines: Should be disposed of following local environmental regulations to prevent pollution.

Conclusion: Why Choose Shell Tellus 33?

Shell Tellus 33 embodies a blend of high-quality formulation, proven performance, and industry compliance. Its optimal viscosity, excellent stability, and robust additive package make it suitable for a wide range of hydraulic systems, from industrial machinery to mobile equipment.

Key reasons to select Shell Tellus 33:

- Ensures smooth, efficient hydraulic operation.
- Extends equipment lifespan through superior wear and oxidation protection.
- Reduces maintenance costs and downtime.
- Meets stringent international standards for safety and performance.

Investing in Shell Tellus 33 means prioritizing reliability, safety, and efficiency—a choice that pays dividends over the lifespan of your hydraulic systems.

In summary, whether you're operating heavy machinery, maintaining industrial systems, or managing mobile equipment, understanding the detailed specifications of Shell Tellus 33 helps in making informed decisions. Its well-balanced properties, compliance with global standards, and proven track record position it as a top-tier hydraulic oil for diverse applications.

Question What are the main specifications of the Shell Tellus 33 hydraulic oil? Shell Tellus 33 is a high-quality anti-wear hydraulic oil formulated with mineral base oils and advanced additives, featuring a viscosity of approximately 33 cSt at 40°C, suitable for a wide range of hydraulic systems. **What applications is Shell Tellus 33 suitable for?** Shell Tellus 33 is ideal for industrial hydraulic systems, mobile equipment, and machinery that require a stable, anti-wear hydraulic fluid with good oxidation stability and corrosion protection. **What is the viscosity grade of Shell Tellus 33?** Shell Tellus 33 has a viscosity grade of ISO 46, corresponding to its approximate kinematic viscosity of 33 cSt at 40°C. **Does Shell Tellus 33 provide anti-wear protection?** Yes, Shell Tellus 33 contains anti-wear additives that help protect hydraulic system components from wear and extend equipment life. **Is Shell Tellus 33 compatible with other hydraulic oils?** Compatibility depends on the specific oils involved; generally, Shell recommends thorough testing before mixing with other hydraulic fluids to ensure performance and prevent system issues. **What are the key performance benefits of using Shell Tellus 33?** Key benefits include excellent wear protection, good oxidation stability, corrosion prevention, and good filterability, which contribute to longer equipment life and reduced maintenance costs. **What are the operating temperature ranges for Shell Tellus 33?** Shell Tellus 33 performs well within a temperature range of approximately -20°C to +80°C, maintaining fluid stability and lubrication properties within this range. **Is Shell Tellus 33 environmentally friendly?** Shell Tellus 33 is designed to meet industry standards for environmental safety, but users should follow proper disposal and handling procedures as per local regulations. **What certifications or standards does Shell Tellus 33 meet?** Shell Tellus 33 complies with various industry standards such as DIN 51524 Part 2 (HLP), ISO 6743-4 HM, and others, ensuring high-quality performance in hydraulic systems. **How often should Shell Tellus 33 be replaced or changed?** The oil change interval depends on system conditions and operating hours, but typically, Shell recommends inspecting and replacing hydraulic oil every 1,000 to 2,000 hours of operation or as specified by equipment manufacturers.

Related keywords: Shell Tellus 33, hydraulic oil, hydraulic fluid, industrial lubricant, hydraulic oil specifications, Shell lubricants, hydraulic oil viscosity, hydraulic fluid properties, industrial oils, machinery lubrication

Read the full article online: [Shell Tellus 33 Specs](#)